

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
26 May 2005 (26.05.2005)

PCT

(10) International Publication Number
WO 2005/048271 A1

(51) International Patent Classification⁷: **G21C 17/017**,
G01N 29/04, 29/22, F16L 55/00

[CA/CA]; 3814, Parc Lafontaine, Montréal, Québec H2L 3M6 (CA). **ROUSSEAU, Gilles** [CA/CA]; 6270, de la Loire, Anjou, Quebec H1K 3L7 (CA).

(21) International Application Number:
PCT/CA2004/001956

(74) Agent: **ROBIC**; Centre CDP Capital, Bloc E - 8th Floor, 1001, Square Victoria, Montréal, Quebec H2Z 2B7 (CA).

(22) International Filing Date:
12 November 2004 (12.11.2004)

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2,449,477 14 November 2003 (14.11.2003) CA

(71) Applicant (*for all designated States except US*): **HYDRO-QUEBEC** [CA/CA]; 75, boul. René-Lévesque Ouest, Montréal, Quebec H2Z 1A4 (CA).


(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **LAVOIE, Eric**

[Continued on next page]

(54) Title: **MOTORIZED BRACELET ASSEMBLY FOR MOVING SENSOR MODULES AROUND A PIPE**



(57) Abstract: A motorized bracelet assembly for ultrasonic crack detection in a pipe. The bracelet has a motorized frame adapted for installation around the pipe and a sliding arrangement slideably mounted onto the frame. The sliding arrangement guides a displacement of sensor modules in periphery of the pipe. A first driving device controllably drives the sliding arrangement and thereby displacing the sensor modules in periphery of the pipe at desired operating positions. The bracelet comprises biasing devices for biasing the sensor modules against the pipe and a second driving device for controllably driving the frame along the axial direction of the pipe at a desired operating position.



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*